

# Global Leader in Engineering and R&D Services

## A Use case of intelligent maintenance

Agnes Fritsch Solution Director agnes.fritsch@altran.com



### 3 expertise domains to engineer tomorrow

Our Global Service Lines help the world's largest innovators engineer the products and services of tomorrow by leveraging our experts, labs, tools and frameworks around the globe.

Intelligent Maintenance is at the intersection of:









## We work with global innovation leaders across industries.



Automotive









Aeronautics

**AIRBUS** 

SAFRAN

Space. & Naval







Defense





Rail, Infrastructure

& Transport





edf

**ENGIE** 











Industrial & Consumer









Life Sciences

gsk

SANOFI



Communications





vodafone





Semiconductor & Electronics

Qualcom

Thermo Fisher



Internet



Finance & Public Sector















### Let's put a focus on our client Orano





# PREVENT AUTOMATED ARM OUTAGE

EQUIPMENT INSTALLED IN A CRITICAL ENVIRONMENT

TELESCOPIC MECHANICAL ARMS





#### **USE CASE:**

COLLECTING DATA FROM AN
AUTOMATED ARM TO REDUCE
BREADOWNS OCCURRENCES ON
LEGACY SYSTEMS
NOT ONLY ABOUT IT, PEOPLE MATTER

# REAL TIME ASSET MEASUREMENT


ROTATIONS, SPEED, MECHANICAL CONSTRAINTS

#### **DEPLOYED**

TRAINING INTELLIGENT MAINTENANCE PREDICT FAILURES



#### Connected maintenance with IoT on legacy systems



ISO 55000 family standards
ISO 13374 series of standards


Connected maintenance adding data to legacy systems with IoT solutions makes sense:

- Equipment area not easily accessible
- From corrective (fail and fix) to conditional maintenance
- Adding diagnostic and monitoring for:
  - Preventing/predicting
  - Learning, self-learning
  - Training


Cost efficiency of adding IoT rather than changing the machine fleet (up to 1000 machines)



#### **AUTOMATED ARMS in the NUCLEAR INDUSTRY**




MT 200, master slave telescopic mechanical arm, suitable for high capacity and heavy remote manipulations (20 daN).





### **AUTOMATED ARMS in the NUCLEAR INDUSTRY: 1st challenge**



### First challenge: Modelling and choice of the sensors:

- 1. and 2. inertial sensors (X, Y)
- 3. Counterweight Distance measurements (ZMAN/ZE) (Z): IR sensor + Button
- Constraint: putting the sensors on the « cold » zone requires calculating the real » movements on the « hot » zone and not measuring directly
- 5. Modelling requires defining critical parameters and assessing relevant thresholds

Designing and adding a set of sensors and data collectors:

- To measure the subsystems movement
- To collect and transmit the data via a wireless infrastructure
- To expose the results: MMI offering a visualization of angles X/Y, Z, ZMAN/ZE, the thresholds detection, the utilization rates








### **AUTOMATED ARMS in the NUCLEAR INDUSTRIAL: 2nd challenge**

Adding the IoT without interferences, disturbance or reduction of the MTBF





# 



Conclusion : le Ze est reconstitué correctement à +/-100mr

#### Second challenge: designing and bringing connectivity

- First trial: using LoRa2.4 GHz (sensors + GTW)
- Second trial: moving to LoRa 868 MHz technology for the alerts + WiFi for the connectivity + using wired sensors => OK and complying to the standards
- Interfacing to the command of the MT200 without compromising security features => synchronize the supervision card with NTP
- Modelling for the integration feasibility
- Powering the sensor set-up without having interferences between both systems
- Compliance to the standards

Real time constraints: LoRa Alerts, WiFi (not done yet), kinetics calculations are not done on the edge (data collected every 100ms)







### **AUTOMATED ARMS in the NUCLEAR INDUSTRY: 3rd challenge**

#### Collecting the data, checking the relevancy, creating value

Third challenge: collecting the data to create value:

- Checking the data and algorithms relevance: Euler angles (Tait Bryan with pitch/roll/yaw like evalutation) was sufficient, no need to use quaternions.
- Analysis of failure causes: quantifying critical parameters and thresholds (Orano)
- Anticipation of failures (combining utilization rates and large movements detection above thresholds
- Training the collaborators: the client will combine training sessions of collaborators with data signatures and references collected by the IoT system.

#### Cost efficiency:

- Remplacing 1000 arms vs equipping them with the IoT system: cost of the "arm" .vs. 1600 to 2000 Euros for the IoT solution.
- Average failure cost is huge compared to setting this IoT solution (not disclosed by Orano)
- Mutualization of the maintenance operations brings a huge benefit (not disclosed by Orano)









